10/561,438

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT

## (19) World Intellectual Property Organization International Bureau



## 

(43) International Publication Date 27 January 2005 (27.01.2005)

(10) International Publication Number WO 2005/008757 A1

(51) International Patent Classification7: 33/00, 21/338, 29/812

H01L 21/28.

(21) International Application Number:

PCT/JP2004/010556

(22) International Filing Date:

16 July 2004 (16.07.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2003-197927 60/489,108

16 July 2003 (16.07.2003) 23 July 2003 (23.07.2003)

(71) Applicant (for all designated States except US): SHOWA DENKO K.K. [JP/JP]; 13-9, Shiba Daimon 1-chome, Minato-ku, Tokyo 1058518 (JP).

(72) Inventor; and

(75) Inventor/Applicant (for US only): UDAGAWA, Takashi [JP/JP]; c/o SHOWA DENKO K.K., 1505, Oaza Shimokagemori, Chichibu-shi, Saitama 3691871 (JP).

(74) Agents: AOKI, Atsushi et al.; A. AOKI, ISHIDA & AS-SOCIATES, Toranomon 37 Mori Bldg., 5-1, Toranomon 3-chome, Minato-ku, Tokyo 1058423 (JP).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Published:

with international search report

[Continued on next page]

(54) Title: n-TYPE OHMIC ELECTRODE FOR n-TYPE GROUP III NITRIDE SEMICONDUCTOR, SEMICONDUCTOR LIGHT-EMITTING DEVICE WITH THE ELECTRODE, AND METHOD FOR FORMING n-TYPE OHMIC ELECTRODE



(57) Abstract: The present invention provides a constitution of ntype ohmic electrode suitable for n-type group III nitride semiconductor, and a forming method thereof for providing low contact resistivity. The n-type ohmic electrode is provided to comprise an alloy of aluminum and lanthanum or comprises lanthanum at the junction interface with the n-type group III nitride semiconductor. The method comprising forming a lanthanum-aluminum alloy layer at 300°C or less to form an n-type ohmic electrode enriched in lanthanum at the junction interface.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.